

- Mobile Pentium processor 300MHz (Cache 32KB Integrated)
- 32MB (Max. 160MB) SDRAM
- 512KB(PipeLined Burst SRAM)
- 4.3GB
- 3.5", 1.44MB/720KB (External)
- Optional 24x (Max.)
- 12.1" TFT Color Display, 800 x 600 dots
- 256bit - Bit NeoMagic™ 2200 Multimedia Graphics Controller Video RAM 2.5MB(SGRAM)
(Internal) 800x600 16.7M Colors,
(External) 640x480 16.7M Colors , 800x600 16.7M Colors, 1,024x768 64K Colors , 1,280x1,024
256 Colors
- Keyboard 84-key Ergonomic Keyboard
- AccuPoint





CPU	Mobile Pentium Processor 233MHz , (Cache 32KB Integrated)
Memory	32MB (Max. 160MB) EDO DRAM
CACHE	512KB Pipelined burst SRAM level 2 cache
Hard Disk Drive	4.0GB (Max. 8.0GB)
Floppy Disk Drive	3.5", 1.44MB/720KB, or 2nd HDD or 2nd Battery Pack
CD-ROM Drive	20x (Max.)
Display	12.1" ,TFT Color Display, 800x600 dots
Display Controller	S3 ViRGE MX 86C260 (3D graphics supported)
Resolution (Internal)	800x600 16.7M Colors , 1,024x768 64K Colors (Virtual display) 1,280x1,024 256 Colors (Virtual display)
Resolution (External)	640x480 16.7M Colors , 800x600 16.7M Colors , 1,024x768 64K Colors , 1,280x1,024 256 Colors
Video RAM	2MB (SGRAM)
Keyboard	84-key Ergonomic Keyboard , 101 US ASCII Keyboard compatible
Pointing Device	AccuPoint
Standard Interface	Serial (16550UART), Parallel(ECP), USB, RGB, PS/2, Keyboard / PS2 Mouse, External FDD, Expansion Bus, External, Microphone, Headphone, Line-in
PC Card Slots	Type x1 or Type x2 (ZV port and CardBus supports)
Interfaced Capability	Fast Infrared (4Mbps)
Sound	Integrated SoundBlaster Pro Windows Sound System compatible (3D Sound supported), Internal System Speakers(stereo), Internal Microphone (monaural)
Modem	K56 Flex voice/data/fax modem
Security	Security Lock Port, Power on Password, Supervisor password, Keyboard Lock, Screen Blank
Power	Auto Resume, Max Time Power Management, ACPI-ready
Battery Type	Li-ion
Battery Life *	Full Power Mode: 2.0H + 4 hours (2 batteries)
Recharges	2-3H (Power off) / 4-10H (Power on)
Power Supply	Univ.AC Adapter(100-240V) (standard), ACP ver 1.0 ready
Weight	3.2 (kg) (w/battery pack,FDD) 3.3 (kg) (w/battery pack & CD- ROMDrive)
Dimensions	304 x 239 x 52 (mm)
Pre-installed Software	Microsoft Windows 95, CardWorks, IntelliSync97 LANDisk , Client Manager 32(CD-ROM bundled), Microsoft Internet Explorer 4.01, Toshiba Utilities: MaxTime and Fn-esse, RingZero RingCentral, AT&T WorldNet
Worldwide Warranty	Valid for 3 year from date of purchase.
Attachments	AC Adapter, Power Cord, Satellite Pro 490CDT/490XCDT User's Guide, Microsoft Windows 95 Manual, CD-ROMDrive, External Floppy Disk Drive, FDD Attachment Case, Recovery CD