

15-110 Recitation Week 7

Reminders

- 10/24 Tue - Check3/HW3 revisions due (Tuesday after break)
- [Reci feedback form](#)
- Have a restful and rejuvenating break!

Overview

- Big-O Exercise
- For Loop Review
- Dictionary Review
- Tree Code Writing
- Dictionary Code Writing

Problems

BIG-O EXERCISE

Calculate the Big-O for the following examples:

Returning the last character in a string	
<pre>def powersOfTwo(n): # n = n m = 1 while m <= n: print(m) m *= 2</pre>	
<pre>def foo(L): # len(L) = n if L == []: return 0 else: L.append(L[0]) n = L.index(10) L.pop(0) return n # .index(), .pop() are O(n) worst case!</pre>	
<pre>#You are guaranteed L is a nxn 2D list def tripleLoop(L): for i in range(20): for row in L: for elem in row: print(elem)</pre>	

FOR EACH LOOP REVIEW

Notes on Loops::

Problem:

Use the following code to answer the questions:

```
s = "15-110"  
for i in range(len(s)):  
    print(i)  
for i in s:  
    print(i)
```

What does the code print?

What is the type of i for each loop?

DICTIONARY REVIEW

Notes on dictionaries:

Here is an example of a type of problem that uses dictionaries. Read through the problem statement and solution and note the key points of the code.

Problem:

Kelly's Bakery is doing an inventory of their freshly baked goods. This morning, they baked new items and now they need to update their inventory to represent these items. You are given a dictionary that represents the inventory at Kelly's Bakery, which maps the name of the item to how many items of that baked good are available. Write the function `updateInventory(d, newItems)` that takes the current inventory and a new dictionary called `newItems` and updates it accordingly. The function should also handle the case that there is an item in `newItems` that doesn't exist in `d`.

Solution:

```
def updateInventory(d, newItems):
    for item in newItems:
        if item in d:
            d[item] += newItems[item]
        else:
            d[item] = newItems[item]
    return d
```

TREE CODE WRITING

Write the function `addEvenLeaves(t)` that takes in a dictionary representation of a tree (you can assume it will have at least 1 node) and returns a sum of **only** the even values held by leaves.

```
def addEvenLeaves(tree):  
    # base case: leaf node  
    if _____ and _____:  
        # check if leaf's value is even  
        if _____:  
            # returns the leaves value  
            return _____  
        else:  
            # what should you return if the leaf isn't even?  
            return _____  
    else:  
        value = 0  
        # recursive case if left subtree is not None  
        if _____:  
            value += _____  
        # recursive case if right subtree is not None  
        if _____:  
            value += _____  
    return value
```

DICTIONARY CODE WRITING

Given a dictionary that maps teams like CMU, Pitt, OSU, PennState, and another unspecified number of football teams, to the number of wins they have, we return the team with the most wins. There will be no ties. For example,

`mostWins({"CMU": 1, "Pitt": 1, "OSU": 3, "PennState": 1})` returns "OSU".

```
def mostWins(wins):  
    # Initialize variables to store the team that has won  
    # the most so far and how many times they had won  
    mostWinTeam = _____  
    mostWins = _____  
    # Loop through the dictionary  
    for _____ in _____:  
        # What do we do if the current team has won more  
        # than the team with the most wins so far?  
        if _____ > mostWins:  
            mostWins = _____  
            mostWinTeam = _____  
    # Return the team that has won the most  
    return mostWinTeam
```