

Full Name: \_\_\_\_\_

Andrew ID: \_\_\_\_\_ Section: \_\_\_\_\_

## 15–210: Parallel and Sequential Data Structures and Algorithms

### PRACTICE FINAL (SOLUTIONS)

May 2017

- **Verify:** There are 23 pages in this examination, comprising 8 questions worth a total of 152 points. The last 2 pages are an appendix with costs of sequence, set and table operations.
- **Time:** You have 180 minutes to complete this examination.
- **Goes without saying:** Please answer all questions in the space provided with the question. Clearly indicate your answers.
- **Beware:** You may refer to your two double-sided  $8\frac{1}{2} \times 11$ in sheets of paper with notes, but to no other person or source, during the examination.
- **Primitives:** In your algorithms you can use any of the primitives that we have covered in the lecture. A reasonably comprehensive list is provided at the end.
- **Code:** When writing your algorithms, you can use ML syntax but you don't have to. You can use the pseudocode notation used in the notes or in class. For example you can use the syntax that you have learned in class. In fact, in the questions, we use the pseudo rather than the ML notation.

---

#### Sections

---

<b>A</b>	9:30am - 10:20am	Andra/Charles
<b>B</b>	10:30am - 11:20am	Aashir/Anatol
<b>C</b>	12:30pm - 1:20pm	Oliver
<b>D</b>	12:30pm - 1:20pm	Rohan/Serena
<b>E</b>	1:30pm - 2:20pm	John/Christina
<b>F</b>	1:30pm - 4:20pm	Vivek/Teddy
<b>G</b>	3:30pm - 5:20pm	Ashwin/Sunny

---

Full Name: \_\_\_\_\_ Andrew ID: \_\_\_\_\_

Question	Points	Score
Binary Answers	30	
Costs	12	
Short Answers	26	
Slightly Longer Answers	20	
Semidynamic MST's	20	
Median ADT	12	
Geometric Coverage	12	
Swap with Compare-and-Swap	20	
Total:	152	

**Question 1: Binary Answers** (30 points)

- (a) (2 points) **TRUE** or **FALSE**: The expressions `(Seq.reduce f I A)` and `(Seq.iterate f I A)` always return the same result as long as `f` is commutative.

**Solution:** FALSE

- (b) (2 points) **TRUE** or **FALSE**: The expressions `(Seq.reduce f I A)` and `(Seq.reduce f I (Seq.reverse A))` always return the same result if `f` is associative and commutative.

**Solution:** TRUE

- (c) (2 points) **TRUE** or **FALSE**: If a randomized algorithm has expected  $O(n)$  work, then there exists some constant  $c$  such that the work performed is guaranteed to be at most  $cn$ .

**Solution:** FALSE

- (d) (2 points) **TRUE** or **FALSE**: Solving recurrences with induction can be used to show both upper and lower bounds?

**Solution:** TRUE

- (e) (2 points) **TRUE** or **FALSE**: Let  $p$  be an odd prime. In open address hashing with a table of size  $p$  and given a hash function  $h(k)$ , quadratic probing uses  $h(k, i) = (h(k) + i^2) \bmod p$  as the  $i$ th probe position for key  $k$ . If there is an empty spot in the table quadratic hashing will always find it.

**Solution:** FALSE

- (f) (2 points) **TRUE** or **FALSE**: Bottom-Up Dynamic Programming can be parallel, whereas the Top-Down version as described in class (ie, purely functional) is always sequential.

**Solution:** TRUE

- (g) (2 points) **TRUE** or **FALSE**: The height of any treap is  $O(\log n)$ .

**Solution:** FALSE

- (h) (2 points) **TRUE** or **FALSE**: It is possible to write insert for treaps that uses the split operation but not the join operation.

**Solution:** TRUE

- (i) (2 points) **TRUE** or **FALSE**: Dijkstra's algorithm always terminates even if the input graph contains negative edge weights.

**Solution:** TRUE

- (j) (2 points) **TRUE** or **FALSE**: A  $\Theta(n^2)$ -work algorithm always takes longer to run than a  $\Theta(n \log n)$ -work algorithm.

**Solution:** FALSE

- (k) (2 points) **TRUE** or **FALSE**: We can improve the work efficiency of a parallel algorithm by using granularity control.

**Solution:** TRUE

- (l) (2 points) **TRUE** or **FALSE**: We can measure the work efficiency of a parallel algorithm by measuring the running time (work) of the algorithm on a single core, divided by the running time (work) of the sequential elision of the algorithm.

**Solution:** FALSE

- (m) (2 points) **TRUE** or **FALSE**: Some atomic read-modify-write operations such as compare-and-swap suffer from the ABA problem.

**Solution:** TRUE

- (n) (2 points) **TRUE** or **FALSE**: Race conditions are just when two concurrent threads write to the same location.

**Solution:** FALSE

- (o) (2 points) **TRUE** or **FALSE**: In a greedy scheduler a processor cannot sit idle if there is work to do.

**Solution:** TRUE

**Question 2: Costs** (12 points)

- (a) (6 points) Give tight asymptotic bounds ( $\Theta$ ) for the following recurrence using the tree method. Show your work.

$$W(n) = 2W(n/2) + n \log n$$

**Solution:** At  $i^{\text{th}}$  level there are  $2^i$  subproblems each of which cost is  $\frac{n}{2^i} \log \frac{n}{2^i}$  for total cost of  $n(\log n - i)$ .

$$\begin{aligned} W(n) &= \sum_{i=0}^{\log n - 1} n(\log n - i) \\ &= n \sum_{j=1}^{\log n} j \\ &= n \log n (\log n + 1) / 2 \\ W(n) &\in \Theta(n \log^2 n) \end{aligned}$$

- (b) (6 points) Check the appropriate column for each row in the following table:

	root dominated	leaf dominated	balanced
$W(n) = 2W(n/2) + n^{1.5}$			
$W(n) = \sqrt{n}W(\sqrt{n}) + \sqrt{n}$			
$W(n) = 8W(n/2) + n^2$			

**Solution:**

	root dominated	leaf dominated	balanced
$W(n) = 2W(n/2) + n^{1.5}$	X		
$W(n) = \sqrt{n}W(\sqrt{n}) + \sqrt{n}$		X	
$W(n) = 8W(n/2) + n^2$		X	

### Question 3: Short Answers (26 points)

Answer each of the following questions in the spaces provided.

- (a) (3 points) What simple formula defines the parallelism of an algorithm (in terms of work and span)?

**Solution:**  $P(n) = \frac{W(n)}{S(n)}$

- (b) (3 points) Name two algorithms we covered in this course that use the greedy method.

**Solution:** Dijkstra's, Prim's, Kruskal's ...

- (c) (3 points) Given a sequence of key-value pairs  $A$ , what does the following code do?

```
Table.map Seq.length (Table.collect A)
```

**Solution:** Makes a histogram of  $A$  mapping each key to how many times it appears (the values are ignored).

- (d) (5 points) Consider an undirected graph  $G$  with unique positive weights. Suppose it has a minimum spanning tree  $T$ . If we square all the edge weights and compute the MST again, do we still get the same tree structure? Explain briefly.

**Solution:** Yes we get the same tree. The minimum spanning tree only depends on the ordering among the edges. This is because the only thing we do with edges is compare them.

- (e) (3 points) What asymptotically efficient parallel algorithm/technique can one use to count the number of trees in a forest (tree and forest have their graph-theoretical meaning)? (*Hint: the ancient saying of "can't see forest from the trees" may or may not be of help.*) Give the work and span for your proposed algorithm.

**Solution:** Run tree contraction over the entire forrest to contract each tree into a single vertex. (You can use either star contract or rake and compress.) Count the number of vertices at the end.

$$W(n) = O(n) \quad S(n) = O(\log^2 n)$$

expected case.


- (f) (3 points) What are the two ordering invariants of a Treap? (Describe them briefly.)

**Solution: Heap property:** Each node has a higher priority than all of its descendants.

**BST property:** Each node's key is greater than the keys in its left subtree and less than the keys in its right subtree.

- (g) (6 points) Is it the case that in a leftist heap the left subtree of a node is always larger than the right subtree. If so, argue why (briefly). If not, give an example.

**Solution:** False, as shown by the following example of a shape of a leftist heap:



**Question 4: Slightly Longer Answers** (20 points)

- (a) (6 points) Certain locations on a straight pathway recently built for robotics research have to be covered with a special surface, so CMU hires a contractor who can build arbitrary length segments to cover these locations (a location is covered if there is a segment covering it). The segment between  $a$  and  $b$  (inclusive) costs  $(b - a)^2 + k$ , where  $k$  is a non-negative constant. Let  $k \geq 0$  and  $X = \langle x_0, \dots, x_{n-1} \rangle$ ,  $x_i \in \mathbb{R}_+$ , be a sequence of locations that have to be covered. Give an  $O(n^2)$ -work dynamic programming solution to find the cheapest cost of covering these points (all given locations must be covered). Be sure to specify a recursive solution, identify sharing, and describe the **work** and **span** in terms of the DAG.

**Solution:**

```
function CCC(X) =
let
  % The cheapest cover cost for X[0, ..., i]
  function f(i) =
    if (i < 0) then 0
    else min_{0 ≤ j ≤ i} (f(j - 1) + k + (x_i - x_j)^2)
  in f(|X| - 1) end
```

**Sharing:**

There are at most  $|X| = n$  distinct subcalls to  $f$  since  $i$  ranges from 0 to  $n - 1$ .

**DAG and costs:**

Each node in the DAG does work  $O(n)$  and has span  $O(\log n)$ . The DAG has depth and size  $O(n)$ . Therefore the total work is  $O(n^2)$  and the total span is  $O(n \log n)$ .

- (b) (7 points) Here is a slightly modified version of the algorithm given in class for finding the optimal binary search tree (OBST):

```
function OBST (A) =
let
  function OBST' (S, d) =
    if |S| = 0 then 0
    else min_{i ∈ {1, ..., |S|}} (OBST' (S_{1, i-1}, d + 1) + d × p(S_i) + OBST' (S_{i+1, |S|}, d + 1))
  in
    OBST' (A, 1)
end
```

Recall that  $S_{i,j}$  is the subsequence  $\langle S_i, S_{i+1}, \dots, S_j \rangle$  of  $S$ . For  $|A| = n$ , place an asymptotic upper bound on the number of distinct arguments OBST' will have (a tighter bound will get more credit).

**Solution:** There are  $\binom{n+1}{2} = n(n+1)/2$  possible subsequences of  $S$  and  $d$  is between 1 and  $n$ , so the number of distinct arguments is upper-bounded by  $O(n^3)$ .

- (c) (7 points) Given  $n$  line segments in 2 dimensions, the 3-intersection problem is to determine if any three of them intersect at the same point. Explain how to do this in  $O(n^2)$



work and  $O(\log^2 n)$  span. You can assume the lines are given with integer endpoints (i.e. you can do exact arithmetic and not worry about roundoff errors).

**Solution:** First, we compute all possible intersection points between pairs of line segments. There can be at most  $O(n^2)$  points. Then, insert these points into a hash table, checking if any collision seen is a result of 3 lines intersecting at the same point. This meets the time bound since hashing  $O(n^2)$  points takes  $O(n^2)$  work and  $O(\log^2 n^2) \subseteq O(\log^2 n)$  span.

**Question 5: Semidynamic MST's** (20 points)

Recall that a minimum spanning forest (MSF) of a graph is a collection of minimum spanning trees, one for each connected component of the graph.

You are given a data type called `DynamicForest` that supports the following operations on undirected, weighted forests  $F$ . Let  $(u, v, w)$  denote an undirected edge between  $u$  and  $v$  with weight  $w$ . Throughout this question, you may assume that edge weights are **unique**.

For a forest  $F$  with  $n$  vertices, each of the following operations has  $O(\log n)$  work and span, except for **init**, which has  $O(n)$  work.

- **init**  $V$ : Initialize and return a forest with vertices  $V$  and no edges.
- **maxEdge**  $F (u, v)$ : Return (SOME  $e$ ) where  $e$  is the heaviest (largest weight) edge on the path from  $u$  to  $v$  in  $F$  if such  $e$  exists, return NONE if no such  $e$  exists. For example, if  $u$  and  $v$  are not connected, then the function returns NONE.
- **deleteEdge**  $F (u, v)$ : If there is an edge between  $u$  and  $v$  in  $F$ , delete it and return the new forest. Otherwise, return  $F$  unmodified.
- **insertEdge**  $F (u, v, w)$ : Assuming  $u$  and  $v$  are not already connected in  $F$ , insert the edge  $(u, v, w)$  and return the updated forest. If  $u$  and  $v$  are connected, then this function immediately aborts and initiates the apocalypse. Do not allow this to happen.

In all parts of this problem, you will be graded on clarity in addition to correctness, so **think before you write**.

- (a) (5 points) Argue in  $\leq 4$  *clear* sentences that, given any cycle in a graph, the maximum edge on the cycle **cannot** be in the MST. **Note:** If you can't get this, you may still use this fact in the rest of the problem.

**Solution:** Proof by contradiction: assume the maximum edge  $e = (u, v)$  is in the MST. If we remove  $e$  from the MST then the two disconnected components define a cut in the graph. Since  $u$  and  $v$  are on a cycle there is an edge  $e' \neq e$  in the graph on a path from  $u$  to  $v$ , which crosses the cut. Now, replace  $e$  in the MST with  $e'$  to bridge the cut and obtain a spanning tree, which is lighter than the original, so we have a contradiction.

**Common problems:** Failing to invoke that there is a cycle and not explaining that there are multiple edges across any cut.

(b) (7 points) Write the following function (in SML or pseudocode):

**extendMSF** : DynamicForest \* edge  $\rightarrow$  DynamicForest

Given  $F$  which is the MSF of the graph  $(V, E)$ , **extendMSF**  $(F, (u, v, w))$  should return the MSF of the graph  $(V, E \cup \{(u, v, w)\})$ . Your implementation should have  $O(\log |V|)$  work and span.

**fun** extendMSF (F, (u,v,w)) =

**case** \_\_\_\_\_ **of**

NONE  $\Rightarrow$  \_\_\_\_\_

SOME \_\_\_\_\_  $\Rightarrow$

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Solution:**

```
fun extendMSF (F, (u,v,w)) =  
  case maxEdge F (u,v) of  
    NONE => insertEdge F (u,v,w)  
  | SOME (um,vm,wm) =>  
    if w < wm  
    then insertEdge (deleteEdge F (um,vm)) (u,v,w)  
    else F
```

**Common problems:** miss match the edge type for (SOME  $e$ ).

- (c) (3 points) Argue in just a few sentences why your answer to the previous part is correct.

**Solution:** If  $u$  and  $v$  are not already connected, then the edge  $(u, v, w)$  is clearly the lightest edge between the connected components of  $u$  and  $v$  and therefore must be in the MSF.

If  $u$  and  $v$  are already connected, then by part (a) we know that the maximum edge on the cycle formed by adding  $(u, v, w)$  is not in the MST. This maximum edge is either  $(u, v, w)$ , or the maximum edge in the current path between  $u$  and  $v$ . We check which is smaller and keep it.

- (d) (5 points) Write **one line** of code to compute the minimum spanning forest of a graph  $(V, E)$ . Your implementation should have  $O(|V| + |E| \log |V|)$  work and should use **extendMSF**. You may assume  $E$  is represented as an edge sequence.

```
fun makeMSF (V,E) =
```

---

**Solution:**

```
fun makeMSF (V,E) =  
  iterate extendMSF (init V) E
```

**Question 6: Median ADT** (12 points)

The *median* of a set  $C$ , denoted by  $\text{median}(C)$ , is the value of the  $\lceil n/2 \rceil$ -th smallest element (counting from 1). For example,

$$\begin{aligned}\text{median}(\{1, 3, 5, 7\}) &= 3 \\ \text{median}(\{4, 2, 9\}) &= 4\end{aligned}$$

In this problem, you will implement an abstract data type `medianT` that maintains a collection of integers (possibly with duplicates) and supports the following operations:

<code>insert(C, v)</code>	: <code>medianT × int → medianT</code>	add the integer $v$ to $C$ .
<code>median(C)</code>	: <code>medianT → int</code>	return the median value of $C$ .
<code>fromSeq(S)</code>	: <code>int Seq.t → medianT</code>	create a <code>medianT</code> from $S$ .

Throughout this problem, let  $n$  denote the size of the collection at the time, i.e.,  $n = |C|$ .

- (a) (5 points) Describe how you would implement the `medianT` ADT using (balanced) binary search trees so that `insert` and `median` take  $O(\log n)$  work and span.

**Solution:** As described in the augmented tree lecture, we keep a balanced BST where each node is augmented with the size of the subtree, so that the  $(n/2)$ -th element can be found in  $O(\log n)$ ; inserting an element also takes  $O(\log n)$  because we simply need to “update” the size information on a relevant path, which has length  $O(\log n)$ .

- (b) (7 points) Using some other data structure, describe how to improve the work to  $O(\log n)$ ,  $O(1)$  and  $O(|S|)$  for the three operations respectively. The `fromSeq S` function needs to run in  $O(\log^2 |S|)$  expected span and the work can be expected case. (*Hint: think about maintaining the median, the elements less than the median, and the elements greater than the median separately.*)

**Solution:** Keep a max heap of values smaller than the median, the current median, and a min heap of values bigger than the median. When inserting, put the new value in the correct heap, rebalancing as necessary. The function `fromSeq` can be easily supported since using quick select to the initial median only requires  $O(n)$  expected work and  $O(\log^2 n)$  span. The build heaps can be done in the same work and span using a meldable heap such as leftist heaps.

**Question 7: Geometric Coverage** (12 points)

For points  $p_1, p_2 \in \mathbb{R}^2$ , we say that  $p_1 = (x_1, y_1)$  *covers*  $p_2 = (x_2, y_2)$  if  $x_1 \geq x_2$  and  $y_1 \geq y_2$ . Given a set  $S \subseteq \mathbb{R}^2$ , the *geometric cover number* of a point  $q \in \mathbb{R}^2$  is the number of points in  $S$  that  $q$  covers. Notice that by definition, every point covers itself, so its cover number must be at least 1.

In this problem, we'll compute the geometric cover number for every point in a given sequence. More precisely:

**Input:** a sequence  $S = \langle s_1, \dots, s_n \rangle$ , where each  $s_i \in \mathbb{R}^2$  is a 2-d point.

**Output:** a sequence of pairs each consisting of a point and its cover number. Each point must appear exactly once, but the points can be in any order.

Assume that we use the `ArraySequence` implementation for sequences.

- (a) (4 points) Develop a brute-force solution `gcnBasic` (in pseudocode or Standard ML). Despite being a brute-force solution, your solution should not do more work than  $O(n^2)$ .

**Solution:**

```

fun GCN S =
  let fun covers((x1, y1), (x2, y2)) = (x1 ≥ x2) ∧ (y1 ≥ y2)
  in
    ⟨ (p, |⟨ p' ∈ P | covers(p, p') ⟩|) : p ∈ P ⟩
  end

```

- (b) (4 points) In words, outline an algorithm `gcnImproved` that has  $O(n \log n)$  work. You may assume an implementation of `OrderedTable` in which `split`, `join`, and `insert` have  $O(\log n)$  cost (i.e., work and span), and `size` and `empty` have  $O(1)$  cost.

**Solution:** We'll keep an ordered table  $T$  of points ordered by their  $x$  values. Initially,  $T$  is empty. To compute the cover number for every point, we'll first sort these points by their  $y$  values. Then, for each of these points, we insert them one by one into  $T$ —and the cover number of this point can be found by splitting  $T$  using its  $x$  value and taking the size of the left side. This assumes we can calculate size in  $O(\log n)$  work, which is easy with an augmented tree implementation of ordered tables.

- (c) (4 points) Show that the work bound cannot be further improved by giving a lower bound for the problem.

**Solution:** We'll reduce comparison-based sorting to GCN, which means that GCN cannot be solved in less than  $\Omega(n \log n)$  work. The reduction is as follows: for a given input sequence  $s = \langle s_1, \dots, s_n \rangle$ , we create a sequence of points

$$P = \langle (s_1, s_1), (s_2, s_2), \dots, (s_n, s_n) \rangle$$

(using map in  $O(n)$  work and  $O(1)$  span). Running GCN on this  $P$  gives the “rank” of each element, which we can then use as indices to inject and get a sorted sequence.



**Question 8: Swap with Compare-and-Swap** (20 points)

- (a) (10 points) Write a function `swap` that takes two memory locations  $la$  and  $lb$  and atomically swaps their values using compare-and-swap. Recall that compare-and-swap takes a memory location  $\ell$ , an old value  $v$ , and a new value  $w$  and atomically replaces the contents of  $\ell$  with  $w$  if the contents of  $\ell$  is equal to  $v$ .

```
long lock = 0;

function swap-with-cas (la: long, lb: long) =
let
  function take_lock () =
    while (true) do
      if compare-and-swap (lock, 0, 1) then
        break;

  function release_lock () =
    while (true) do
      if compare-and-swap (lock, 1, 0) then
        break;

in
  take_lock ();
  long x <- load lx
  long y <- load ly
  store y into lx
  store x into ly
  release_lock ();
end
```

- (b) (10 points) Does your algorithm suffer from the ABA problem? If so, explain how it does, and whether the problem affects the correctness of your algorithm. If so, then can you describe briefly a way to fix the problem (no pseudo-code needed)?

**Solution:** Yes it does, because the contents of `lock` can change between the load and the compare-and-swap to 1 and then back to 0. This however does not effect correctness because the atomicity is still guaranteed, because when the `lock` is 0, there is no other thread is the criticas section.

But if we still want to fix the ABA problem, then we can do so by making sure that each update to the location `lock` increments some version number. We would then insist on having the same version number during compare and swap. This would reduce the chances of the ABA problem but would not absolutely prevent it.

## Appendix: Library Functions

```
signature SEQUENCE =
sig
  type 'a t
  type 'a seq = 'a t
  type 'a ord = 'a * 'a -> order
  datatype 'a listview = NIL | CONS of 'a * 'a seq
  datatype 'a treeview = EMPTY | ONE of 'a | PAIR of 'a seq * 'a seq

  exception Range
  exception Size

  val nth : 'a seq -> int -> 'a
  val length : 'a seq -> int
  val toList : 'a seq -> 'a list
  val toString : ('a -> string) -> 'a seq -> string
  val equal : ('a * 'a -> bool) -> 'a seq * 'a seq -> bool

  val empty : unit -> 'a seq
  val singleton : 'a -> 'a seq
  val tabulate : (int -> 'a) -> int -> 'a seq
  val fromList : 'a list -> 'a seq

  val rev : 'a seq -> 'a seq
  val append : 'a seq * 'a seq -> 'a seq
  val flatten : 'a seq seq -> 'a seq

  val filter : ('a -> bool) -> 'a seq -> 'a seq
  val map : ('a -> 'b) -> 'a seq -> 'b seq
  val zip : 'a seq * 'b seq -> ('a * 'b) seq
  val zipWith : ('a * 'b -> 'c) -> 'a seq * 'b seq -> 'c seq

  val enum : 'a seq -> (int * 'a) seq
  val filterIdx : (int * 'a -> bool) -> 'a seq -> 'a seq
  val mapIdx : (int * 'a -> 'b) -> 'a seq -> 'b seq
  val update : 'a seq * (int * 'a) -> 'a seq
  val inject : 'a seq * (int * 'a) seq -> 'a seq

  val subseq : 'a seq -> int * int -> 'a seq
  val take : 'a seq -> int -> 'a seq
  val drop : 'a seq -> int -> 'a seq
  val splitHead : 'a seq -> 'a listview
  val splitMid : 'a seq -> 'a treeview

  val iterate : ('b * 'a -> 'b) -> 'b -> 'a seq -> 'b
  val iteratePrefixes : ('b * 'a -> 'b) -> 'b -> 'a seq -> 'b seq * 'b
  val iteratePrefixesIncl : ('b * 'a -> 'b) -> 'b -> 'a seq -> 'b seq
  val reduce : ('a * 'a -> 'a) -> 'a -> 'a seq -> 'a
  val scan : ('a * 'a -> 'a) -> 'a -> 'a seq -> 'a seq * 'a
  val scanIncl : ('a * 'a -> 'a) -> 'a -> 'a seq -> 'a seq

  val sort : 'a ord -> 'a seq -> 'a seq
  val merge : 'a ord -> 'a seq * 'a seq -> 'a seq
  val collect : 'a ord -> ('a * 'b) seq -> ('a * 'b seq) seq
```

```

val collate : 'a ord -> 'a seq ord
val argmax : 'a ord -> 'a seq -> int

val $ : 'a -> 'a seq
val % : 'a list -> 'a seq
end

```

<b>ArraySequence</b>	Work	Span
empty ()		
singleton a		
length s	$O(1)$	$O(1)$
nth s i		
subseq s (i, len)		
tabulate f n if $f(i)$ has $W_i$ work and $S_i$ span	$O\left(\sum_{i=0}^{n-1} W_i\right)$	$O\left(\max_{i=0}^{n-1} S_i\right)$
map f s if $f(s[i])$ has $W_i$ work and $S_i$ span, and $ s  = n$		
zipWith f (s, t) if $f(s[i], t[i])$ has $W_i$ work and $S_i$ span, and $\min( s ,  t ) = n$		
reduce f b s if f does constant work and $ s  = n$	$O(n)$	$O(\lg n)$
scan f b s if f does constant work and $ s  = n$		
filter p s if p does constant work and $ s  = n$		
flatten s	$O\left(\sum_{i=0}^{n-1} (1 +  s[i] )\right)$	$O(\lg  s )$
sort cmp s if cmp does constant work and $ s  = n$	$O(n \lg n)$	$O(\lg^2 n)$
merge cmp (s, t) if cmp does constant work, $ s  = n$ , and $ t  = m$	$O(m + n)$	$O(\lg(m + n))$
append (s, t) if $ s  = n$ , and $ t  = m$	$O(m + n)$	$O(1)$

```

signature TABLE =
sig
  structure Key : EQKEY
  structure Seq : SEQUENCE

  type 'a t
  type 'a table = 'a t

  structure Set : SET where Key = Key and Seq = Seq

  val size : 'a table -> int
  val domain : 'a table -> Set.t
  val range : 'a table -> 'a Seq.t
  val toString : ('a -> string) -> 'a table -> string
  val toSeq : 'a table -> (Key.t * 'a) Seq.t

  val find : 'a table -> Key.t -> 'a option
  val insert : 'a table * (Key.t * 'a) -> 'a table
  val insertWith : ('a * 'a -> 'a) -> 'a table * (Key.t * 'a) -> 'a table
  val delete : 'a table * Key.t -> 'a table

  val empty : unit -> 'a table
  val singleton : Key.t * 'a -> 'a table
  val tabulate : (Key.t -> 'a) -> Set.t -> 'a table
  val collect : (Key.t * 'a) Seq.t -> 'a Seq.t table
  val fromSeq : (Key.t * 'a) Seq.t -> 'a table

  val map : ('a -> 'b) -> 'a table -> 'b table
  val mapKey : (Key.t * 'a -> 'b) -> 'a table -> 'b table
  val filter : ('a -> bool) -> 'a table -> 'a table
  val filterKey : (Key.t * 'a -> bool) -> 'a table -> 'a table

  val reduce : ('a * 'a -> 'a) -> 'a -> 'a table -> 'a
  val iterate : ('b * 'a -> 'b) -> 'b -> 'a table -> 'b
  val iteratePrefixes : ('b * 'a -> 'b) -> 'b -> 'a table -> ('b table * 'b)

  val union : ('a * 'a -> 'a) -> ('a table * 'a table) -> 'a table
  val intersection : ('a * 'b -> 'c) -> ('a table * 'b table) -> 'c table
  val difference : 'a table * 'b table -> 'a table

  val restrict : 'a table * Set.t -> 'a table
  val subtract : 'a table * Set.t -> 'a table

  val $ : (Key.t * 'a) -> 'a table
end

```

```

signature SET =
sig
  structure Key : EQKEY
  structure Seq : SEQUENCE

  type t
  type set = t

  val size : set -> int
  val toString : set -> string
  val toSeq : set -> Key.t Seq.t

  val empty : unit -> set
  val singleton : Key.t -> set
  val fromSeq : Key.t Seq.t -> set

  val find : set -> Key.t -> bool
  val insert : set * Key.t -> set
  val delete : set * Key.t -> set

  val filter : (Key.t -> bool) -> set -> set

  val reduceKey : (Key.t * Key.t -> Key.t) -> Key.t -> set -> Key.t
  val iterateKey : ('a * Key.t -> 'a) -> 'a -> set -> 'a

  val union : set * set -> set
  val intersection : set * set -> set
  val difference : set * set -> set

  val $ : Key.t -> set
end

```

<b>MkTreapTable</b>	Work	Span
size $T$	$O(1)$	$O(1)$
filter $f T$ map $f T$	$\sum_{(k \mapsto v) \in T} W(f(v))$	$\lg  T  + \max_{(k \mapsto v) \in T} S(f(v))$
tabulate $f X$	$\sum_{k \in X} W(f(k))$	$\max_{k \in X} S(f(k))$
reduce $f b T$ if $f$ does constant work	$O( T )$	$O(\lg  T )$
insertWith $f (T, (k, v))$ if $f$ does constant work find $T k$ delete $(T, k)$	$O(\lg  T )$	$O(\lg  T )$
domain $T$ range $T$ toSeq $T$	$O( T )$	$O(\lg  T )$
collect $S$ fromSeq $S$	$O( S  \lg  S )$	$O(\lg^2  S )$

For each argument pair  $(A, B)$  below, let  $n = \max(|A|, |B|)$  and  $m = \min(|A|, |B|)$ .

<b>MkTreapTable</b>	Work	Span
union $f (X, Y)$ intersection $f (X, Y)$ difference $(X, Y)$ restrict $(T, X)$ subtract $(T, X)$	$O(m \lg(\frac{n+m}{m}))$	$O(\lg(n + m))$